




ELECTRICAL DATA/STC			
Model Type		CE-30M30	CE-33M30
Peak Power(Pmax)		30	33
Maximum Power Voltage (Vmp)		17.1	17.7
Maximum Power Currenty (Imp)		1.75	1.86
Open Circuit Voltage (Voc)		20.1	20.7
Short Circuit Voltage (Isc)		1.94	2.07
Module Efficiency (%)		18.1	19.9
Output cables		Without cables and connectors	
Packing:5pcs/box			
Cell Type	No. of Cells	Dimensions	Weight
Monocrystalline	30	240*690*17mm	1.7kg

CE-30M30/CE-33M30




PACKING INFORMATION

- 20FT container
- 16Pallets/8064PCS
- 40HQ container
- 54Pallets/14850PCS

ELECTRICAL DATA/STC			
Model Type		CE-33M32	CE-35M32
Peak Power(Pmax)		33	35
Maximum Power Voltage (Vmp)		18.2	18.9
Maximum Power Currenty (Imp)		1.81	1.85
Open Circuit Voltage (Voc)		21.4	22.1
Short Circuit Voltage (Isc)		2.00	2.06
Module Efficiency (%)		18.6	19.7
Output cables		Without cables and connectors	
Packing:5pcs/box			
Cell Type	No. of Cells	Dimensions	Weight
Monocrystalline	32	240*740*17mm	1.8kg

CE-33M32/CE-35M32




PACKING INFORMATION

- 20FT container
- 14Pallets/7056PCS
- 40HQ container
- 27Pallets/13608PCS

ELECTRICAL DATA/STC			
Model Type		CE-40M32	CE-45M32
Peak Power(Pmax)		40	45
Maximum Power Voltage (Vmp)		18.2	18.9
Maximum Power Currenty (Imp)		2.19	2.38
Open Circuit Voltage (Voc)		21.4	22.1
Short Circuit Voltage (Isc)		2.42	2.65
Module Efficiency (%)		18.9	21.3
Output cables		Without cables and connectors	
Packing:5pcs/box			
Cell Type	No. of Cells	Dimensions	Weight
Monocrystalline	32	450*470*17mm	2.2kg

CE-40M32/CE-45M32




PACKING INFORMATION

- 20FT container
- 16Pallets/6048PCS
- 40HQ container
- 30Pallets/11340PCS



ELECTRICAL DATA/STC			
Model Type		CE-55M32	CE-60M32
Peak Power(Pmax)		55	60
Maximum Power Voltage (Vmp)		18.2	18.9
Maximum Power Currenty (Imp)		3.02	3.18
Open Circuit Voltage (Voc)		21.4	22.1
Short Circuit Voltage (Isc)		3.33	3.53
Module Efficiency (%)		19.9	21.7
Output cables		Without cables and connectors	
Packing:5pcs/box			
Cell Type	No. of Cells	Dimensions	Weight
Monocrystalline	32	450*615*17mm	2.9kg

CE-55M32/CE-60M32




PACKING INFORMATION

- 20FT container
- 18Pallets/4284PCS
- 40HQ container
- 34Pallets/8568PCS

ELECTRICAL DATA/STC			
Model Type		CE-60M30	CE-67M30
Peak Power(Pmax)		60	67
Maximum Power Voltage (Vmp)		17.1	17.7
Maximum Power Currenty (Imp)		3.51	3.79
Open Circuit Voltage (Voc)		20.1	20.7
Short Circuit Voltage (Isc)		3.88	4.20
Module Efficiency (%)		19.0	21.3
Output cables		Without cables and connectors	
Packing:5pcs/box			
Cell Type	No. of Cells	Dimensions	Weight
Monocrystalline	30	450*700*17mm	3.3kg

CE-60M30/CE-67M30




PACKING INFORMATION

- 20FT container
- 16Pallets/4032PCS
- 40HQ container
- 30Pallets/7560PCS

ELECTRICAL DATA/STC			
Model Type		CE-65M32	CE-72M32
Peak Power(Pmax)		65	72
Maximum Power Voltage (Vmp)		18.2	18.9
Maximum Power Currenty (Imp)		3.56	3.81
Open Circuit Voltage (Voc)		21.4	22.1
Short Circuit Voltage (Isc)		3.94	4.23
Module Efficiency (%)		19.5	21.6
Output cables		Without cables and connectors	
Packing:5pcs/box			
Cell Type	No. of Cells	Dimensions	Weight
Monocrystalline	32	450*740*17mm	3.5kg

CE-65M32/CE-72M32




PACKING INFORMATION

- 20FT container
- 14Pallets/3432PCS
- 40HQ container
- 29Pallets/7308PCS



ELECTRICAL DATA/STC			
Model Type		CE-75M30	CE-85M30
Peak Power(Pmax)		75	85
Maximum Power Voltage (Vmp)		17.1	17.7
Maximum Power Currenty (Imp)		4.39	4.80
Open Circuit Voltage (Voc)		20.1	20.7
Short Circuit Voltage (Isc)		4.85	5.33
Module Efficiency (%)		19.6	22.2
Output cables		Without cables and connectors	
Packing:5pcs/box			
Cell Type	No. of Cells	Dimensions	Weight
Monocrystalline	30	450*850*25mm	4.0kg

CE-75M30/CE-85M30




PACKING INFORMATION

- 20FT container
- 14Pallets/2236PCS
- 40HQ container
- 26Pallets/5590PCS

ELECTRICAL DATA/STC			
Model Type		CE-80M32	CE-90M32
Peak Power(Pmax)		80	90
Maximum Power Voltage (Vmp)		18.2	18.9
Maximum Power Currenty (Imp)		4.39	4.77
Open Circuit Voltage (Voc)		21.4	22.1
Short Circuit Voltage (Isc)		4.85	5.29
Module Efficiency (%)		19.5	22.0
Output cables		Without cables and connectors	
Packing:5pcs/box			
Cell Type	No. of Cells	Dimensions	Weight
Monocrystalline	32	450*910*25mm	4.3kg

CE-80M32/CE-90M32




PACKING INFORMATION

- 20FT container
- 12Pallets/2064PCS
- 40HQ container
- 24Pallets/5160PCS

ELECTRICAL DATA/STC			
Model Type		CE-100M30	CE-110M30
Peak Power(Pmax)		100	110
Maximum Power Voltage (Vmp)		17.1	17.7
Maximum Power Currenty (Imp)		5.85	6.21
Open Circuit Voltage (Voc)		20.1	20.7
Short Circuit Voltage (Isc)		6.46	6.90
Module Efficiency (%)		19.8	21.8
Output cables		Without cables and connectors	
Packing:5pcs/box			
Cell Type	No. of Cells	Dimensions	Weight
Monocrystalline	30	450*1120*25mm	5.3kg

CE-100M30/CE-110M30




PACKING INFORMATION

- 20FT container
- 20Pallets/1720PCS
- 40HQ container
- 34Pallets/4472PCS



ELECTRICAL DATA/STC			
Model Type		CE-110M32	CE-120M32
Peak Power(Pmax)		110	120
Maximum Power Voltage (Vmp)		18.2	18.9
Maximum Power Currenty (Imp)		6.03	6.36
Open Circuit Voltage (Voc)		21.4	22.1
Short Circuit Voltage (Isc)		6.66	7.06
Module Efficiency (%)		20.5	22.4
Output cables		Without cables and connectors	
Packing:5pcs/box			
Cell Type	No. of Cells	Dimensions	Weight
Monocrystalline	32	450*1190*25mm	5.6kg

CE-110M32/CE-120M32




PACKING INFORMATION

- 20FT container
- 18Pallets/1462PCS
- 40HQ container
- 38Pallets/4038PCS

ELECTRICAL DATA/STC			
Model Type		CE-150M30	CE-170M30
Peak Power(Pmax)		150	170
Maximum Power Voltage (Vmp)		17.1	17.7
Maximum Power Currenty (Imp)		8.77	9.60
Open Circuit Voltage (Voc)		20.1	20.7
Short Circuit Voltage (Isc)		9.69	10.67
Module Efficiency (%)		20.2	22.9
Output cables		Without cables and connectors	
Packing:5pcs/box			
Cell Type	No. of Cells	Dimensions	Weight
Monocrystalline	30	1110*670*25mm	7.8kg

CE-150M30/CE-170M30




PACKING INFORMATION

- 20FT container
- 10Pallets/1290PCS
- 40HQ container
- 38Pallets/2962PCS

ELECTRICAL DATA/STC			
Model Type		CE-165M33	CE-185M33
Peak Power(Pmax)		165	185
Maximum Power Voltage (Vmp)		18.8	19.5
Maximum Power Currenty (Imp)		8.77	9.50
Open Circuit Voltage (Voc)		22.1	22.8
Short Circuit Voltage (Isc)		9.69	10.55
Module Efficiency (%)		20.2	22.6
Output cables		Without cables and connectors	
Packing:5pcs/box			
Cell Type	No. of Cells	Dimensions	Weight
Monocrystalline	33	1220*670*25mm	8.6kg

CE-165M33/CE-185M33




PACKING INFORMATION

- 20FT container
- 10Pallets/1118PCS
- 40HQ container
- 56Pallets/2408PCS



ELECTRICAL DATA/STC			
Model Type		CE-160M32	CE-180M32
Peak Power(Pmax)		160	180
Maximum Power Voltage (Vmp)		18.2	18.9
Maximum Power Currenty (Imp)		8.77	9.53
Open Circuit Voltage (Voc)		21.4	22.1
Short Circuit Voltage (Isc)		9.69	10.59
Module Efficiency (%)		20.3	22.9
Output cables		Without cables and connectors	
Packing:5pcs/box			
Cell Type	No. of Cells	Dimensions	Weight
Monocrystalline	32	895*880*25mm	8.3kg

CE-160M32/CE-180M32




PACKING INFORMATION

- 20FT container 12Pallets/1032PCS
- 40HQ container 26Pallets/2652PCS

ELECTRICAL DATA/STC			
Model Type		CE-200M60	CE-225M60
Peak Power(Pmax)		200	225
Maximum Power Voltage (Vmp)		34.2	35.4
Maximum Power Currenty (Imp)		5.85	6.36
Open Circuit Voltage (Voc)		40.2	41.4
Short Circuit Voltage (Isc)		6.46	7.06
Module Efficiency (%)		20.3	22.8
Output cables		Without cables and connectors	
Packing:5pcs/box			
Cell Type	No. of Cells	Dimensions	Weight
Monocrystalline	60	1120*880*25mm	10.3kg

CE-200M60/CE-225M60




PACKING INFORMATION

- 20FT container 20Pallets/860PCS
- 40HQ container 26Pallets/2236PCS

ELECTRICAL DATA/STC			
Model Type		CE-220M64	CE-240M64
Peak Power(Pmax)		220	240
Maximum Power Voltage (Vmp)		36.5	37.8
Maximum Power Currenty (Imp)		6.03	6.36
Open Circuit Voltage (Voc)		42.9	44.2
Short Circuit Voltage (Isc)		6.66	7.06
Module Efficiency (%)		21.0	22.9
Output cables		Without cables and connectors	
Packing:5pcs/box			
Cell Type	No. of Cells	Dimensions	Weight
Monocrystalline	64	1190*880*25mm	11kg

CE-220M64/CE-240M64




PACKING INFORMATION

- 20FT container 19Pallets/817PCS
- 40HQ container 39Pallets/1981PCS



ELECTRICAL DATA/STC			
Model Type		CE-240M48	CE-270M48
Peak Power(Pmax)		240	270
Maximum Power Voltage (Vmp)		27.4	28.3
Maximum Power Currenty (Imp)		8.77	9.53
Open Circuit Voltage (Voc)		32.2	33.1
Short Circuit Voltage (Isc)		9.69	10.59
Module Efficiency (%)		20.7	23.2
Output cables		Without cables and connectors	
Packing:5pcs/box			
Cell Type	No. of Cells	Dimensions	Weight
Monocrystalline	48	1320*880*25mm	12.2kg

CE-240M48/CE-270M48




PACKING INFORMATION

- 20FT container 16Pallets/688PCS
- 40HQ container 34Pallets/1734PCS

ELECTRICAL DATA/STC			
Model Type		CE-260M52	CE-290M52
Peak Power(Pmax)		260	290
Maximum Power Voltage (Vmp)		29.6	30.7
Maximum Power Currenty (Imp)		8.77	9.45
Open Circuit Voltage (Voc)		34.8	35.9
Short Circuit Voltage (Isc)		9.69	10.50
Module Efficiency (%)		20.7	23.0
Output cables		Without cables and connectors	
Packing:5pcs/box			
Cell Type	No. of Cells	Dimensions	Weight
Monocrystalline	52	1430*880*25mm	13.2kg

CE-260M52/CE-290M52




PACKING INFORMATION

- 20FT container 16Pallets/688PCS
- 40HQ container 32Pallets/1632PCS

ELECTRICAL DATA/STC			
Model Type		CE-280M56	CE-315M56
Peak Power(Pmax)		280	315
Maximum Power Voltage (Vmp)		31.9	33.0
Maximum Power Currenty (Imp)		8.77	9.53
Open Circuit Voltage (Voc)		37.5	38.6
Short Circuit Voltage (Isc)		9.69	10.59
Module Efficiency (%)		20.7	23.3
Output cables		Without cables and connectors	
Packing:5pcs/box			
Cell Type	No. of Cells	Dimensions	Weight
Monocrystalline	56	1535*880*30mm	14.3kg

CE-280M56/CE-315M56




PACKING INFORMATION

- 20FT container 14Pallets/504PCS
- 40HQ container 30Pallets/1286PCS

ELECTRICAL DATA/STC			
Model Type		CE-300M60	CE-335M60
Peak Power(Pmax)		300	335
Maximum Power Voltage (Vmp)		34.2	35.4
Maximum Power Currenty (Imp)		8.77	9.46
Open Circuit Voltage (Voc)		40.2	41.4
Short Circuit Voltage (Isc)		9.69	10.51
Module Efficiency (%)		20.7	23.1
Output cables		Without cables and connectors	
Packing:5pcs/box			
Cell Type	No. of Cells	Dimensions	Weight
Monocrystalline	60	1650*880*30mm	15.4kg

CE-300M60/CE-335M60



PACKING INFORMATION

- 20FT container 12Pallets/432PCS
- 40HQ container 28Pallets/1204PCS